


有效行程	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1050	1100
L	466	516	566	616	666	716	776	816	866	916	966	1016	1066	1116	1166	1216	1266	1316	1366	1416	1466	1516
A	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50
M	0	1	1	1	1	2	2	2	2	3	3	3	3	4	4	4	4	5	5	5	5	6
N	4	6	6	6	6	8	8	8	8	10	10	10	10	12	12	12	12	14	14	14	14	16
参考重量g	13.2	15	16.8	17.6	18.4	19.1	19.9	20.7	21.5	22.2	23	23.8	24.6	25.3	26.1	26.9	27.7	28.4	29.2	30	30.8	31.6

设计		电话	
标准化		日期	2021-11-30
校核		日期	
审批		日期	

 <div> <div>瑞翔智能</div> <div>RUIXIANG TECH</div> </div>		<div> <div>东莞瑞翔智能科技有限公司</div> <div>Dongguan RuiXiang Intelligent Technology Co., Ltd.</div> </div>			
	视 图	单 位	比 例	零件类别：成品	
2021-11-30		mm	1:5	材 料：6063-T5	
	共 张 第 张	版本：A		重量：	数量：1